


## STAGE LIGHTING

Extra-Flex Entertainment Industry and Stage Lighting Cable  
105°C 600 Volt UL Type SC and CSA Type PPC

<p><b>APPLICATION:</b> Portable power systems, entertainment industry activities. Other similar applications that would require temporary power.</p> <p><b>STANDARDS:</b> UL Listed, CSA Certified MSHA Approved, RoHS Compliant</p> <p><b>CONSTRUCTION:</b> 8 through 4/0 AWG fully annealed stranded bare copper per ASTM B-174. Black neoprene jacket.</p>							
USAWC Part #	AWG SIZE	Nominal Strand	NOMINAL O.D.		Current Amps	Approx Net Weight lbs/1000 ft	Copper Weight lbs/1000 ft
			INCHES	mm			
8-01SC	8	162/30	.385	9.78	80	115	52
6-01SC	6	259/30	.430	10.92	105	150	78
4-01SC	4	418/30	.475	12.06	140	210	128
2-01SC	2	660/30	.560	14.22	190	300	201
1-01SC	1	836/30	.580	14.73	220	365	247
1/0-01SC	1/0	1056/30	.635	16.13	260	440	312
2/0-01SC	2/0	1320/30	.665	16.89	300	555	397
3/0-01SC	3/0	1672/30	.690	17.53	350	640	510
4/0-01SC	4/0	2090/30	.780	19.81	405	805	660